



Inch table

Dimensions in: inches - millimeters

¹ d ₁	² d ₂ Thread		d ₃	h ₁	h ₂	h ₃ ≈	h ₄ Stroke	l ₂	t min.
0.55 14	10 x 32	1/4 x 20	0.39 10	0.98 25	0.18 4.5	1.38 35	0.14 3.5	1.77 45	0.35 9
0.71 18	1/4 x 20	5/16 x 18	0.53 13.5	1.22 31	0.26 6.5	1.77 45	0.16 4	2.44 62	0.43 11
0.87 22	5/16 x 18	3/8 x 16	0.63 16	1.42 36	0.31 8	2.05 52	0.16 4	2.91 74	0.55 14
0.98 25	3/8 x 16	1/2 x 13	0.75 19	1.69 43	0.43 11	2.48 63	0.16 4	3.50 89	0.67 17

Metric table

Dimensions in: millimeters - inches

¹ d ₁	² d ₂ Thread		d ₃	h ₁	h ₂	h ₃ ≈	h ₄ Stroke	l ₂	t min.
14 0.55	M 5	M 6	10 0.39	25 0.98	4.5 0.18	35 1.38	3.5 0.14	45 1.77	9 0.35
18 0.71	M 6	M 8	13.5 0.53	31 1.22	6.5 0.26	45 1.77	4 0.16	62 2.44	11 0.43
22 0.87	M 8	M 10	16 0.63	36 1.42	8 0.31	52 2.05	4 0.16	74 2.91	14 0.55
25 0.98	M 10	M 12	19 0.75	43 1.69	11 0.43	63 2.48	4 0.16	89 3.50	17 0.67
30 1.18	M 12	M 16	23 0.91	50.5 1.99	12 0.47	76 2.99	5 0.20	108 4.25	22 0.87

Specification

- Lever body
Zinc die-cast
- Powder coated
Black, RAL 9005, textured finish **SW**
Orange, RAL 2004, textured finish **OS**
- Tapped insert / retaining screw
Stainless steel AISI 303
- RoHS compliant

Information

GN 101.1 adjustable levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations that can easily be disengaged.
Pulling the lever upwards disengages the serrations, allowing it to be swiveled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

How to order (Inch)	¹	Diameter d ₁
	²	Thread d ₂
	³	Color
GN 101.1-14-10X32-SW		

How to order (Metric)	¹	Diameter d ₁
	²	Thread d ₂
	³	Color
GN 101.1-22-M8-OS		

On request

- Special colors and threads