


Assembly instruction



3 Type

- A Exterior hinge wings
- I Interior hinge wings

4 Identification

- C With countersunk holes

Metric table

1		2		Dimensions in: millimeters - inches												
l ₁		l ₂ - l ₄		d ₁	d ₂	l ₃	l ₅	l ₆	m ₁		m ₂	m ₃	m ₄	m ₅	m ₆	s
Type A	Type I								Type A	Type I						
72	86	125 - 40	165 - 80	6.6	14	40	36	43	40.8	55	42.5	37.5	50	-	-	3.5
2.83	3.39	4.92 - 1.57	6.50 - 3.15	0.26	0.55	1.57	1.42	1.69	1.61	2.17	1.67	1.48	1.97			0.14
72	86	335 - 250	485 - 400	6.6	14	40	36	43	40.8	55	-	-	-	72.5	150	3.5
2.83	3.39	13.12 - 9.84	19.09 - 15.75	0.26	0.55	1.57	1.42	1.69	1.61	2.17				2.85	5.91	0.14

Specification

- Body
Aluminum
Anodized finish, natural color **EL**
- Bearing bushing / cover cap
Plastic
Technopolymer (Polyamide PA)
Gray, RAL 7035
- Tapered dowel pin ISO 8741
Steel, zinc plated, blue passivated finish
- Plastic Characteristics
- RoHS compliant

On request

- Other lengths and hole spacings
- Other finishes

Information

GN 2295 triple winged hinges are made of drawn profiled aluminum and can be used on doors and covers.

External hinge wing, type A hinges, allow mounting with a very small door gap. Type I hinges are mounted between the door gap. This results in the mounting screws being hidden when the door is closed, which reduces the chance of vandalism.

The hinges are delivered loose and must be mounted according to the accompanying instructions. Any hinge combination may be created (if needed, by shortening the middle wing) thanks to the modular design and available accessories.

see also...

- List of Hinge Types
- Product Family Standard Parts for Profile Systems

How to order

GN 2295-72-335-A-C-EL

- 1 Width l₁
- 2 Length l₂ - l₄
- 3 Type
- 4 Identification
- 5 Finish