



Specification



- Lever body
Zinc die-cast
- Powder coated
 - Black, RAL 9005, textured finish ● **SW**
 - Orange, RAL 2004, textured finish ● **OS**
 - Red, RAL 3000, textured finish ● **RS**
 - Silver, RAL 9006, textured finish ● **SR**
- Chrome-plated finish ● **CR**
- Uncoated, slide ground ● **RH**
- Insert / retaining screw
Stainless steel
European Standard No. 1.4305 (AISI 303)
- Spring
Stainless steel
European Standard No. 1.4310 (AISI 301)
- **RoHS compliant**

Information

GN 300.1 adjustable levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations that can easily be disengaged.

Pulling the lever upwards disengages the serrations, allowing it to be swiveled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

see also...

- *Adjustable Levers GN 300 (with Steel Insert)*
- *Adjustable Levers GN 300.5 (Stainless Steel, Matte Shot-Blasted Finish)*
- *Adjustable Levers GN 303.1 (with Push Button)*

On request

- Black, RAL 9011, silk shiny finish ● **SZ**
- Special colors, bores, and threads

How to order (Inch) <div style="display: flex; justify-content: space-around; margin-top: 5px;"> 1 2 3 </div>	1 Lever length l₁ 2 Thread d₁ 3 Color (Finish)
GN 300.1-30-10X32-SW	

How to order (Metric) <div style="display: flex; justify-content: space-around; margin-top: 5px;"> 1 2 3 </div>	1 Lever length l₁ 2 Thread d₁ (Bore d₂) 3 Color (Finish)
GN 300.1-78-M10-OS	

Inch table

Dimensions in: inches - millimeters

l ₁	d ₁ Thread		d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	t min.
1.18 30	10 x 32	1/4 x 20	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5	.31 8
1.77 45	10 x 32	1/4 x 20	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5	.31 8
2.48 63	1/4 x 20	5/16 x 18	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4	.43 11
3.07 78	5/16 x 18	3/8 x 16	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4	.55 14
3.62 92	3/8 x 16	1/2 x 13	.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4	.67 17

Metric table

Dimensions in: millimeters - inches

l ₁	d ₁ Thread			d ₂ H7 Bore		d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	t min.
30 1.18	M 3	-	-	-	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14	7 .28
30 1.18	M 4	M 5	M 6	B 5	B 6	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14	8 .31
45 1.77	M 4	M 5	M 6	B 5	B 6	10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14	8 .31
63 2.48	M 6	M 8	-	B 8	-	13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16	11 .43
78 3.07	M 8	M 10	M 12	B 8	B 10	16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16	14 .55
92 3.62	M 10	M 12	-	B 12	-	19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16	17 .67
108 4.25	M 12	M 16	-	B 12	B 16	23 .91	30 1.18	50.5 1.99	12 .47	75 2.95	5 .20	22 .87