

**4 Type (Base)**

- A0** Without rubber pad / cap
- B0** Without rubber pad / cap, with 2 mounting holes
- A1** With rubber cap, clipped on, black
- A3** With rubber pad, vulcanized, black

**Inch table**

| d <sub>1</sub> | d <sub>2</sub><br>Thread | l <sub>1</sub> |             |             |             |                |             |             |             | l <sub>7</sub><br>Version X | d <sub>3</sub> | h <sub>1</sub> | h <sub>6</sub> | m          | s           |
|----------------|--------------------------|----------------|-------------|-------------|-------------|----------------|-------------|-------------|-------------|-----------------------------|----------------|----------------|----------------|------------|-------------|
|                |                          | Version S / SK |             |             |             | Version U / UK |             |             |             |                             |                |                |                |            |             |
| 1.57<br>40     | 5/16 x 18                | -              | -           | -           | -           | -              | -           | -           | -           | 0.98<br>25                  | 0.21<br>5.4    | 0.08<br>2      | 0.14<br>3.5    | 1.18<br>30 | 0.06<br>1.5 |
| 1.57<br>40     | 3/8 x 16                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.10<br>28                  | 0.21<br>5.4    | 0.08<br>2      | 0.14<br>3.5    | 1.18<br>30 | 0.06<br>1.5 |
| 1.57<br>40     | 1/2 x 13                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.22<br>31                  | 0.21<br>5.4    | 0.08<br>2      | 0.14<br>3.5    | 1.18<br>30 | 0.06<br>1.5 |
| 1.57*<br>40    | 5/8 x 11                 | -              | -           | -           | -           | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | 1.46<br>37                  | 0.21<br>5.4    | 0.08<br>2      | 0.14<br>3.5    | 1.18<br>30 | 0.06<br>1.5 |
| 1.97<br>50     | 5/16 x 18                | -              | -           | -           | -           | -              | -           | -           | -           | 0.98<br>25                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.16<br>4      | 1.50<br>38 | 0.08<br>2   |
| 1.97<br>50     | 3/8 x 16                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.10<br>28                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.16<br>4      | 1.50<br>38 | 0.08<br>2   |
| 1.97<br>50     | 1/2 x 13                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.26<br>32                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.16<br>4      | 1.50<br>38 | 0.08<br>2   |
| 1.97<br>50     | 5/8 x 11                 | -              | -           | -           | -           | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | 1.46<br>37                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.16<br>4      | 1.50<br>38 | 0.08<br>2   |
| 2.36<br>60     | 5/16 x 18                | -              | -           | -           | -           | -              | -           | -           | -           | 0.98<br>25                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.18<br>4.5    | 1.89<br>48 | 0.08<br>2   |
| 2.36<br>60     | 3/8 x 16                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.10<br>28                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.18<br>4.5    | 1.89<br>48 | 0.08<br>2   |
| 2.36<br>60     | 1/2 x 13                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.26<br>32                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.18<br>4.5    | 1.89<br>48 | 0.08<br>2   |
| 2.36<br>60     | 5/8 x 11                 | -              | -           | -           | -           | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | 1.46<br>37                  | 0.26<br>6.6    | 0.10<br>2.5    | 0.18<br>4.5    | 1.89<br>48 | 0.08<br>2   |
| 3.15<br>80     | 5/16 x 18                | -              | -           | -           | -           | -              | -           | -           | -           | 1.02<br>26                  | 0.34<br>8.6    | 0.12<br>3      | 0.20<br>5      | 2.52<br>64 | 0.08<br>2   |
| 3.15<br>80     | 3/8 x 16                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.14<br>29                  | 0.34<br>8.6    | 0.12<br>3      | 0.20<br>5      | 2.52<br>64 | 0.08<br>2   |
| 3.15<br>80     | 1/2 x 13                 | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | -              | -           | -           | -           | 1.26<br>32                  | 0.34<br>8.6    | 0.12<br>3      | 0.20<br>5      | 2.52<br>64 | 0.08<br>2   |
| 3.15<br>80     | 5/8 x 11                 | -              | -           | -           | -           | 2.95<br>75     | 3.94<br>100 | 4.92<br>125 | 5.91<br>150 | 1.50<br>38                  | 0.34<br>8.6    | 0.12<br>3      | 0.20<br>5      | 2.52<br>64 | 0.08<br>2   |
| 3.15<br>80     | 3/4 x 10                 | -              | -           | -           | -           | 3.94<br>100    | 4.92<br>125 | 5.91<br>150 | -           | 1.77<br>45                  | 0.34<br>8.6    | 0.12<br>3      | 0.20<br>5      | 2.52<br>64 | 0.08<br>2   |

\* Not available in type B0

| d <sub>1</sub> | d <sub>2</sub><br>Thread | h <sub>3</sub> | h <sub>4</sub> | A/F <sub>1</sub> | A/F <sub>2</sub> | A/F <sub>3</sub> | A/F <sub>7</sub> | t          |
|----------------|--------------------------|----------------|----------------|------------------|------------------|------------------|------------------|------------|
| 1.57<br>40     | 5/16 x 18                | -              | -              | -                | -                | -                | 1/2              | 0.31<br>8  |
| 1.57<br>40     | 3/8 x 16                 | 0.43<br>11     | -              | 11/16            | -                | -                | 1/2              | 0.39<br>10 |
| 1.57<br>40     | 1/2 x 13                 | 0.43<br>11     | -              | 11/16            | -                | -                | 5/8              | 0.47<br>12 |
| 1.57<br>40     | 5/8 x 11                 | -              | 0.67<br>17     | -                | 1/2              | 5/16             | 7/8              | 0.63<br>16 |
| 1.97<br>50     | 5/16 x 18                | -              | -              | -                | -                | -                | 1/2              | 0.31<br>8  |
| 1.97<br>50     | 3/8 x 16                 | 0.43<br>11     | -              | 11/16            | -                | -                | 1/2              | 0.39<br>10 |
| 1.97<br>50     | 1/2 x 13                 | 0.43<br>11     | -              | 11/16            | -                | -                | 5/8              | 0.47<br>12 |
| 1.97<br>50     | 5/8 x 11                 | -              | 0.67<br>17     | -                | 1/2              | 5/16             | 7/8              | 0.63<br>16 |
| 2.36<br>60     | 5/16 x 18                | -              | -              | -                | -                | -                | 1/2              | 0.31<br>8  |
| 2.36<br>60     | 3/8 x 16                 | 0.43<br>11     | -              | 11/16            | -                | -                | 1/2              | 0.39<br>10 |
| 2.36<br>60     | 1/2 x 13                 | 0.43<br>11     | -              | 11/16            | -                | -                | 5/8              | 0.47<br>12 |
| 2.36<br>60     | 5/8 x 11                 | -              | 0.67<br>17     | -                | 1/2              | 5/16             | 7/8              | 0.63<br>16 |
| 3.15<br>80     | 5/16 x 18                | -              | -              | -                | -                | -                | 1/2              | 0.31<br>8  |
| 3.15<br>80     | 3/8 x 16                 | 0.47<br>12     | -              | 11/16            | -                | -                | 1/2              | 0.39<br>10 |
| 3.15<br>80     | 1/2 x 13                 | 0.47<br>12     | -              | 11/16            | -                | -                | 5/8              | 0.47<br>12 |
| 3.15<br>80     | 5/8 x 11                 | -              | 0.71<br>18     | -                | 1/2              | 5/16             | 7/8              | 0.63<br>16 |
| 3.15<br>80     | 3/4 x 10                 | -              | 0.75<br>19     | -                | 9/16             | 7/16             | 1                | 0.79<br>20 |

3.1

3.2

3.3

3.4

3.5

3.6




3.7

3.8

3.9

3.10



| Stud / socket versions   |  |  |
|--|--|--|
|  <p><b>S</b> Without nut<br/><b>SK</b> With nut</p> |  <p><b>U</b> Without nut<br/><b>UK</b> With nut</p> |  <p><b>X</b> Tapped socket type</p>       |
| External hex at the bottom at $d_2$<br>3/8 x 16, 1/2 x 13<br>M 8, M 10, M 12   | Internal hex at the top, wrench flat at the bottom at $d_2$<br>5/8 x 11, 3/4 x 10<br>M 16, M 20, M 24                                | External hex with tapped socket at $d_2$<br>5/16 x 18, 3/8 x 16, 1/2 x 13, 5/8 x 11, 3/4 x 10<br>M 8, M 10, M 12, M 16, M 20 |

### Metric table

| <b>d<sub>1</sub></b> | <b>d<sub>2</sub></b><br>Thread | <b>l<sub>1</sub></b><br>Version S / SK |            |             |             |             |             |             |             |              |             | <b>l<sub>7</sub></b><br>Version U / UK |             |             |             |            |             |   |   |   |   | <b>d<sub>3</sub></b> | <b>h<sub>1</sub></b> | <b>h<sub>6</sub></b> | <b>m</b> | <b>s</b> |
|----------------------|--------------------------------|--|------------|-------------|-------------|-------------|-------------|-------------|-------------|--------------|-------------|--|-------------|-------------|-------------|------------|-------------|---|---|---|---|----------------------|----------------------|----------------------|----------|----------|
|                      |                                | 40                                     | 50         | 63          | -           | -           | -           | -           | -           | -            | -           | -                                      | -           | -           | -           | -          | -           | - | - | - | - |                      |                      |                      |          |          |
| 40<br>1.57           | M 8                            | 40<br>1.57                             | 50<br>1.97 | 63<br>2.48  | -           | -           | -           | -           | -           | -            | -           | 25<br>0.98                             | 5.4<br>0.21 | 2<br>0.08   | 3.5<br>0.14 | 30<br>1.18 | 1.5<br>0.06 |   |   |   |   |                      |                      |                      |          |          |
| 40<br>1.57           | M 10                           | 50<br>1.97                             | 60<br>2.36 | 80<br>3.15  | 100<br>3.94 | -           | -           | -           | -           | -            | -           | 28<br>1.10                             | 5.4<br>0.21 | 2<br>0.08   | 3.5<br>0.14 | 30<br>1.18 | 1.5<br>0.06 |   |   |   |   |                      |                      |                      |          |          |
| 40<br>1.57           | M 12                           | 60<br>2.36                             | 80<br>3.15 | 100<br>3.94 | 125<br>4.92 | -           | -           | -           | -           | -            | -           | 31<br>1.22                             | 5.4<br>0.21 | 2<br>0.08   | 3.5<br>0.14 | 30<br>1.18 | 1.5<br>0.06 |   |   |   |   |                      |                      |                      |          |          |
| 40*<br>1.57          | M 16                           | -                                      | -          | -           | -           | 75<br>2.95  | 100<br>3.94 | 125<br>4.92 | 150<br>5.91 | 200<br>7.87  | 250<br>9.84 | 37<br>1.46                             | 5.4<br>0.21 | 2<br>0.08   | 3.5<br>0.14 | 30<br>1.18 | 1.5<br>0.06 |   |   |   |   |                      |                      |                      |          |          |
| 50<br>1.97           | M 8                            | 40<br>1.57                             | 50<br>1.97 | 63<br>2.48  | -           | -           | -           | -           | -           | -            | -           | 25<br>0.98                             | 6.6<br>0.26 | 2.5<br>0.10 | 4<br>0.16   | 38<br>1.50 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 50<br>1.97           | M 10                           | 50<br>1.97                             | 60<br>2.36 | 80<br>3.15  | 100<br>3.94 | -           | -           | -           | -           | -            | -           | 28<br>1.10                             | 6.6<br>0.26 | 2.5<br>0.10 | 4<br>0.16   | 38<br>1.50 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 50<br>1.97           | M 12                           | 60<br>2.36                             | 80<br>3.15 | 100<br>3.94 | 125<br>4.92 | -           | -           | -           | -           | -            | -           | 32<br>1.26                             | 6.6<br>0.26 | 2.5<br>0.10 | 4<br>0.16   | 38<br>1.50 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 50<br>1.97           | M 16                           | -                                      | -          | -           | -           | 75<br>2.95  | 100<br>3.94 | 125<br>4.92 | 150<br>5.91 | 200<br>7.87  | 250<br>9.84 | 37<br>1.46                             | 6.6<br>0.26 | 2.5<br>0.10 | 4<br>0.16   | 38<br>1.50 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 60<br>2.36           | M 8                            | 40<br>1.57                             | 50<br>1.97 | 63<br>2.48  | -           | -           | -           | -           | -           | -            | -           | 25<br>0.98                             | 6.6<br>0.26 | 2.5<br>0.10 | 4.5<br>0.18 | 48<br>1.89 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 60<br>2.36           | M 10                           | 50<br>1.97                             | 60<br>2.36 | 80<br>3.15  | 100<br>3.94 | -           | -           | -           | -           | -            | -           | 28<br>1.10                             | 6.6<br>0.26 | 2.5<br>0.10 | 4.5<br>0.18 | 48<br>1.89 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 60<br>2.36           | M 12                           | 60<br>2.36                             | 80<br>3.15 | 100<br>3.94 | 125<br>4.92 | -           | -           | -           | -           | -            | -           | 32<br>1.26                             | 6.6<br>0.26 | 2.5<br>0.10 | 4.5<br>0.18 | 48<br>1.89 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 60<br>2.36           | M 16                           | -                                      | -          | -           | -           | 75<br>2.95  | 100<br>3.94 | 125<br>4.92 | 150<br>5.91 | 200<br>7.87  | 250<br>9.84 | 37<br>1.46                             | 6.6<br>0.26 | 2.5<br>0.10 | 4.5<br>0.18 | 48<br>1.89 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 80<br>3.15           | M 8                            | 40<br>1.57                             | 50<br>1.97 | 63<br>2.48  | -           | -           | -           | -           | -           | -            | -           | 26<br>1.02                             | 8.6<br>0.34 | 3<br>0.12   | 5<br>0.20   | 64<br>2.52 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 80<br>3.15           | M 10                           | 50<br>1.97                             | 60<br>2.36 | 80<br>3.15  | 100<br>3.94 | -           | -           | -           | -           | -            | -           | 29<br>1.14                             | 8.6<br>0.34 | 3<br>0.12   | 5<br>0.20   | 64<br>2.52 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 80<br>3.15           | M 12                           | 60<br>2.36                             | 80<br>3.15 | 100<br>3.94 | 125<br>4.92 | -           | -           | -           | -           | -            | -           | 32<br>1.26                             | 8.6<br>0.34 | 3<br>0.12   | 5<br>0.20   | 64<br>2.52 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 80<br>3.15           | M 16                           | -                                      | -          | -           | -           | 75<br>2.95  | 100<br>3.94 | 125<br>4.92 | 150<br>5.91 | 200<br>7.87  | 250<br>9.84 | 38<br>1.50                             | 8.6<br>0.34 | 3<br>0.12   | 5<br>0.20   | 64<br>2.52 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 80<br>3.15           | M 20                           | -                                      | -          | -           | -           | 75<br>2.95  | 100<br>3.94 | 125<br>4.92 | 150<br>5.91 | 200<br>7.87  | 250<br>9.84 | 45<br>1.77                             | 8.6<br>0.34 | 3<br>0.12   | 5<br>0.20   | 64<br>2.52 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |
| 80<br>3.15           | M 24                           | -                                      | -          | -           | -           | 100<br>3.94 | 125<br>4.92 | 150<br>5.91 | 200<br>7.87 | 300<br>11.81 | -           | -                                      | 8.6<br>0.34 | 3<br>0.12   | 5<br>0.20   | 64<br>2.52 | 2<br>0.08   |   |   |   |   |                      |                      |                      |          |          |

\* Not available in type B0

| d <sub>1</sub> | d <sub>2</sub><br>Thread | h <sub>3</sub> | h <sub>4</sub> | A/F <sub>1</sub> | A/F <sub>2</sub> | A/F <sub>3</sub> | A/F <sub>7</sub> | t          |
|----------------|--------------------------|----------------|----------------|------------------|------------------|------------------|------------------|------------|
| 40<br>1.57     | M 8                      | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 8<br>0.31  |
| 40<br>1.57     | M 10                     | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 10<br>0.39 |
| 40<br>1.57     | M 12                     | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 17<br>0.67       | 12<br>0.47 |
| 40<br>1.57     | M 16                     | -              | 17<br>0.67     | -                | 12<br>0.47       | 8<br>0.31        | 22<br>0.87       | 16<br>0.63 |
| 50<br>1.97     | M 8                      | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 8<br>0.31  |
| 50<br>1.97     | M 10                     | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 10<br>0.39 |
| 50<br>1.97     | M 12                     | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 17<br>0.67       | 12<br>0.47 |
| 50<br>1.97     | M 16                     | -              | 17<br>0.67     | -                | 12<br>0.47       | 8<br>0.31        | 22<br>0.87       | 16<br>0.63 |
| 60<br>2.36     | M 8                      | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 8<br>0.31  |
| 60<br>2.36     | M 10                     | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 10<br>0.39 |
| 60<br>2.36     | M 12                     | 11<br>0.43     | -              | 17<br>0.67       | -                | -                | 17<br>0.67       | 12<br>0.47 |
| 60<br>2.36     | M 16                     | -              | 17<br>0.67     | -                | 12<br>0.47       | 8<br>0.31        | 22<br>0.87       | 16<br>0.63 |
| 80<br>3.15     | M 8                      | 12<br>0.47     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 8<br>0.31  |
| 80<br>3.15     | M 10                     | 12<br>0.47     | -              | 17<br>0.67       | -                | -                | 14<br>0.55       | 10<br>0.39 |
| 80<br>3.15     | M 12                     | 12<br>0.47     | -              | 17<br>0.67       | -                | -                | 17<br>0.67       | 12<br>0.47 |
| 80<br>3.15     | M 16                     | -              | 18<br>0.71     | -                | 12<br>0.47       | 8<br>0.31        | 22<br>0.87       | 16<br>0.63 |
| 80<br>3.15     | M 20                     | -              | 19<br>0.75     | -                | 15<br>0.59       | 10<br>0.39       | 27<br>1.06       | 20<br>0.79 |
| 80<br>3.15     | M 24                     | -              | 22<br>0.87     | -                | 19<br>0.75       | 12<br>0.47       | -                | -          |

**Specification**

- Base  
Steel, zinc plated, blue passivated finish
- Threaded stud / tapped socket  
Steel, zinc plated, blue passivated finish
- Inch size hex nut ANSI / ASME B18.2.2  
Steel, zinc plated, blue passivated finish
- Metric size hex nut ISO 4032  
Steel, zinc plated, blue passivated finish
- Rubber cap  
TPE (Santoprene®) ≈ 80 shore A  
- Clipped on  
- Black
- Rubber pad  
NBR (Perbunan®) 70 ±5 shore A  
- Vulcanized, non-skid  
- Black
- Load Rating Information → page 2120
- Elastomer Characteristics → page 2135
- RoHS compliant


**Information**


GN 40 leveling feet are simple, economically priced components and can be used universally thanks to the wide range of possible combinations of the base and the stud / socket versions. The base with rubber pad / cap protects sensitive surfaces and reduces lateral slippage. The type B0 can also be fastened to the mounting surface via the two mounting holes provided.

These leveling feet are supplied fully assembled and cannot be disassembled.

see also...

- Leveling Feet GN 42 (Steel, with Mounting Hole) → page 1526 / 1530
- Leveling Feet GN 41 (Stainless Steel AISI 304, without Mounting Hole) → page 1520
- Leveling Feet GN 44 / GN 45 (Stainless Steel AISI 316, with / without Mounting Hole) → page 1524 / 1540
- Threaded Tube Ends EN 448 (Plastic) → page 1578 / 1578
- Threaded Tube Inserts GN 992 (Aluminum) → page 1581

|  |  |
|--|--|
| <p>How to order (Inch)</p>  <p><b>GN 40-40-3/8X16-75-A0-S</b></p> | 1 Base diameter d <sub>1</sub>                   |
|  | 2 Thread d <sub>2</sub>                          |
|  | 3 Length l <sub>1</sub> (Length l <sub>7</sub> ) |
|  | 4 Type (Base)                                    |
|  | 5 Stud / socket version                          |

|  |  |
|--|--|
| <p>How to order (Metric)</p>  <p><b>GN 40-80-M20-200-A3-U</b></p> | 1 Base diameter d <sub>1</sub>                   |
|  | 2 Thread d <sub>2</sub>                          |
|  | 3 Length l <sub>1</sub> (Length l <sub>7</sub> ) |
|  | 4 Type (Base)                                    |
|  | 5 Stud / socket version                          |

3.1  
3.2  
3.3  
3.4  
3.5  
3.6  
3.7  
3.8  
3.9  
3.10

