



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d ₁	d ₂ Thread	Length l ≈								d ₄	h ₁	h ₂	h ₃
		16	20	25	30	35	45	-	-				
32 1.26	M 6	.63	.79	.98	1.18	1.38	1.77	-	-	12 .47	20 .79	10 .39	9 .35
40 1.57	M 8	.63	.79	.98	1.18	1.38	1.57	1.77	2.17	14 .55	25 .98	13 .51	10 .39
50 1.97	M 10	.98	1.18	1.38	1.77	2.17	-	-	-	18 .71	32 1.26	20 .79	12 .47
63 2.48	M 12	1.18	1.38	1.57	1.97	2.36	-	-	-	20 .79	40 1.57	25 .98	14 .55

Specification

- Hand knob
Plastic
Technopolymer (Polyamide PA)
- Shock-resistant
- Black, matte finish
- GN 6335.4**
Threaded stud
Steel, zinc plated, blue passivated finish
- GN 6335.5**
Threaded stud
Stainless steel
European Standard No. 1.4305 (AISI 303)
- RoHS compliant

1

TE

Information

GN 6335.4 and GN 6335.5 hand knobs with protruding hub and threaded stud increase the range of application.

Due to the protruding hub and threaded stud being a solid one-piece unit, a strong and secure contact to the clamping surface is created.

see also...

- Hand Knobs GN 6335.4 (without Protruding Hub, with Steel Threaded Stud)
- Hand Knobs GN 6335.5 (without Protruding Hub, with Stainless Steel Threaded Stud)

On request

- Special shorter than listed stud lengths and various stud tips

How to order (Steel threaded stud)

1 2 3 4

GN 6335.4-TE-32-M6-25

1	Material
2	Handle diameter d ₁
3	Thread d ₂
4	Length l

How to order (Stainless steel threaded stud)

1 2 3 4

GN 6335.5-TE-63-M12-60

1	Material
2	Handle diameter d ₁
3	Thread d ₂
4	Length l