



**SS** Stainless Steel

**Metric table**

Dimensions in: millimeters - inches

2		3								
d <sub>1</sub>	NI	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub> ≈	l <sub>4</sub>	s	
KT		Thread								
16 .63	-	M 6	10 .39	13 .51	41.5 1.63	12 .47	4 .16	15 .59	8 .31	
18 .71	18 .71	M 6	10 .39	14.5 .57	56 2.20	13 .51	4 .16	19 .75	8 .31	
22 .87	22 .87	M 8	14 .55	18.5 .73	59 2.32	14 .55	5.2 .20	21 .83	11 .43	
24 .94	24 .94	M 10	14 .55	18.5 .73	74 2.91	16 .63	5.2 .20	27 1.06	11 .43	
25 .98	-	M 10	16 .63	20 .79	84 3.31	16 .63	5.5 .22	30 1.18	13 .51	

**Specification**

- Plastic **KT**  
Technopolymer (Polyamide PA)  
- Temperature resistant up to 194 °F (90 °C)  
- Black, matte finish
- Stainless steel **NI**  
European Standard No. 1.4305 (AISI 303), fine turned
- Threaded spindle  
- Stainless steel  
European Standard No. 1.4305 (AISI 303)
- RoHS compliant

**Information**

GN 798.4 stepped cylindrical revolving handles are noted for their modern design, and the stepped shape provides the operator with a better grip.  
 see also...  
 • *Stepped Retractable Handles GN 798.5 (with Stainless Steel Locking Mechanism)*

How to order <b>GN 798.4-KT-16-M6</b>	1	<b>Material</b>
	2	<b>Handle diameter d<sub>1</sub></b>
	3	<b>Thread d<sub>2</sub></b>

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4

