JW WINCO® A Ganter Company

Series		Characteristics / Features	Materials						Opening angle		Mounting by		
											screwing from		welding
			ST	NI	A4	ZD	AL	KT	Positive	Negative	front	backside	
GN 237 Page 1330 SS Stainless Steel		Accessory available		×	×	×	×		180°	90°	×	×	
GN 237 Page 1331 SS Stainless Steel		Horizontally extended, accessory available		×		×			180°	90°	×	×	
GN 237.3 Page 1332 SS Stainless Steel		With or without centering guides		×					180°	90°	×	×	
GN 237.3 Page 1333 SS Stainless Steel		With or without centering guides, horizontally extended		×					180°	90°	×	×	
EN 237.1 Page 1334		Accessory available						×	180°	90°	×		
GN 437.1 Page 1337		Accessory available				×			180°	90°	×		
GN 136 Page 1338 SS Stainless Steel		Sheet metal, square or vertically extended	×	×					180°	90°	×		×
GN 136 Page 1339 SS Stainless Steel		Sheet metal, horizontally extended	×	×					180°	90°	×		×
GN 1362 Page 1340 SS Stainless Steel		Sheet metal, sturdy		×					180°	90°			×
GN 1364 Page 1341 SS Stainless Steel		Sheet metal, elegant design, sturdy		x					180°	90°	×	×	
GN 1366 Page 1342		Steel profile, very sturdy	x						180°	100°			×
GN 138 Page 1344		Elegant design				×			180°	0°		×	

Series		Characteristics / Features	Materials						Opening angle		Mounting by screwing from		Mounting by welding
			ST	NI	A4	ZD	AL	KT	Positive	Negative	front	backside	
EN 154 www.jwwinco.com		Elegant design						×	180°	0°	×	×	
EN 155 www.jwwinco.com		Elegant design						×	120°	70°	×	×	
EN 157 Page 1345		Elegant design						×	180°	20° resp. 95°	×		
EN 158 www.jwwinco.com		Elegant design						×	180°	90°	×	×	
C Page 1346		Economical, very durable						×	180°	0°	×	×	
EN 151 Page 1347		Elegant design						×	180°	40°	×	×	
EN 151.3 Page 1348		Elegant design						×	180°	20°	×		
EN 151.5 Page 1349		Elegant design						×	180°	20°	×		
GN 2295 Page 1350		For profile systems / panel elements, triple winged					×		∞	∞	×		
GN 2295 Page 1351		For profile systems / panel elements, with extended outer wings, triple winged					×		∞	∞	×		
EN 159 Page 1356		For profile systems						×	180°	100°	×		
EN 159.1 www.jwwinco.com		For profile systems						×	180°	95°	×		

Series		Characteristics / Features	Materials						Opening angle		Mounting by		
											screwing from		welding
			ST	NI	A4	ZD	AL	KT	Positive	Negative	front	backside	
GN 161 www.jwwinco.com		Adjustable, for profile systems						×	180°	90°	×		
GN 129 Page 1358		Corner mounted, two or three parts	×						∞	∞		×	
GN 129.5 www.jwwinco.com SS Stainless Steel		Corner mounted, three parts		×	×				∞	∞		×	
GN 129.2 Page 1359 SS Stainless Steel		Extended, three parts	×	×	×				180°	90°		×	
GN 129.3 www.jwwinco.com		Extended, three parts	×						180°	90°	×		
GN 7231 Page 1364 SS Stainless Steel		Concealed mounting, adjustable, accessory available		x					90°	0°	×	×	×*
GN 7233 Page 1368 SS Stainless Steel		Concealed mounting, adjustable, accessory available		x					120°	0°	×	×	×*
GN 7237 Page 1372 SS Stainless Steel		Concealed mounting, adjustable, accessory available		x					180°	0°	×	×	×*
GN 7241 Page 1384		Concealed mounting, adjustable, accessory available					x		90°	0°	×	×	×**
GN 7243 Page 1388		Concealed mounting, adjustable, accessory available					x		120°	0°	×	×	×**
GN 7247 Page 1392		Concealed mounting, adjustable, accessory available					x		180°	0°	×	×	×**
GN 238 Page 1402		Adjustable, elegant design				×			160°	20°	×		

*With accessory (GN 2376 / GN 2372) **With accessory (GN 7247.4 / GN 7247.6)

JW WINCO® A Ganter Company

Series		Characteristics / Features	Materials						Opening angle		Mounting by screwing from		Mounting by welding
			ST	NI	A4	ZD	AL	KT	Positive	Negative	front	backside	
GN 127 Page 1404		Adjustable				×			170°	90°	×		
GN 235 Page 1405 SS Stainless Steel		Adjustable, accessory available		×		×			180°	15°	×	×	
EN 236 www.jwwinco.com		Adjustable						×	180°	90°	×		
EN 151.4 Page 1406		Adjustable						×	180°	30°	×		
GN 337 Page 1407 SS Stainless Steel		Lift-off, accessory available		×		×			180°	90°	×		
EN 337.1 Page 1408		Lift-off, accessory available						x	180°	90°	x		
GN 2292 Page 1409		For profile systems, with positioning guide					×		∞	∞	×		
GN 2294 Page 1410		For profile systems / panel elements					×		∞	∞	×		
GN 161.1 Page 1411		Lift-off, corner mounted				×		×	∞	∞	×	×	
GN 161.2 www.jwwinco.com		Lift-off				×			180°	0°		×	
EN 160 www.jwwinco.com		Lift-off, with eccentric pin, adjustable						×	∞	∞	×	×	
EN 160.1 Page 1412		Lift-off, with eccentric pin, elegant design						×	180°	0°	×		

*With accessory (GN 2376 / GN 2372) **With accessory (GN 7247.4 / GN 7247.6)

Series		Characteristics / Features	Materials						Opening angle		Mounting by		
											screwing from		welding
			ST	NI	A4	ZD	AL	KT	Positive	Negative	front	backside	
GN 128 Page 1414		Lift-off, corner mounted	×						∞	∞			×
GN 128.2 Page 1415 SS Stainless Steel		Lift-off, corner mounted		×	×		×		∞	∞			×
GN 437 Page 1416		With adjustable friction, accessory available				×			180°	90°	×		
EN 233 Page 1417		With adjustable friction						×	180°	90°	×		
GN 437.4 Page 1418		With 4 indexing positions				×			180°	90°	×		
EN 222 Page 1419		With 4 indexing positions						×	115°	90°	×		
EN 122.1 www.jwwinco.com		With 4 indexing positions						×	180°	15°	×		
EN 122.2 www.jwwinco.com		Without indexing positions						×	180°	15°	×		
GN 437.2 Page 1420		With adjustable lever				×			180°	90°	×		
EN 151.2 Page 1421		With adjustable lever						×	180°	40°	×		
GN 437.3 Page 1422		With spring-loaded return				×			180°	90°	×		
EN 233.3 Page 1423		With or without spring-loaded return						×	180°	90°	×		

Series		Characteristics / Features	Materials						Opening angle		Mounting by		
											screwing from		welding
			ST	NI	A4	ZD	AL	KT	Positive	Negative	front	backside	
EN 233.4 Page XYZ		With or without indexing positions						×	180°	75°	×		
GN 139.1 Page 1424		With integrated safety switch				×			180°	0°		×	
GN 139.2 Page 1424		Without switch				×			180°	0°		×	
GN 139.5 Page 1428 SS Stainless Steel		With integrated safety switch			×				180°	0°		×	
GN 139.6 Page 1428 SS Stainless Steel		Without switch			×				180°	0°		×	
EN 239.6 Page 1430		With integrated safety switch						×	180°	0°	×	×	
EN 239.7 Page 1430		Without switch						×	180°	0°	×	×	
EN 239.4 Page 1434		With integrated switch						×	180°	10°	×		
EN 239.3 Page 1434		Without switch						×	180°	10°	×		