


3 Type

- A Exterior hinge leaf
- I Interior hinge leaf

4 Identification

- C With countersunk holes

Assembly instruction



Metric table

Dimensions in: millimeters - inches

1		2												
l ₁		l ₂	d ₁	d ₂	l ₃	l ₄	l ₅	l ₆	m ₁		m ₂	m ₃	m ₄	s
Type A	Type I								Type A	Type I				
72 2.83	86 3.39	125 4.92	6.6 0.26	14 0.55	40 1.57	40 1.57	36 1.42	43 1.69	40.8 1.61	55 2.17	42.5 1.67	-	-	3.5 0.14
72 2.83	86 3.39	165 6.50	6.6 0.26	14 0.55	40 1.57	80 3.15	36 1.42	43 1.69	40.8 1.61	55 2.17	-	37.5 1.48	50 1.97	3.5 0.14
72 2.83	86 3.39	335 13.19	6.6 0.26	14 0.55	40 1.57	250 9.84	36 1.42	43 1.69	40.8 1.61	55 2.17	-	72.5 2.85	150 5.91	3.5 0.14
72 2.83	86 3.39	485 19.09	6.6 0.26	14 0.55	40 1.57	400 15.75	36 1.42	43 1.69	40.8 1.61	55 2.17	-	72.5 2.85	150 5.91	3.5 0.14

Specification

- Hinge leaf
Aluminum
Anodized finish, natural color **EL**
- Bearing bushing / cover cap
Plastic
Technopolymer (Polyamide PA)
Gray, RAL 7035
- Tapered dowel pin ISO 8741
Steel, zinc plated, blue passivated finish
- Plastic Characteristics → page 2135
- RoHS compliant

Information

GN 2295 triple leaf hinges are made of drawn profiled aluminum and can be used on doors and covers. External hinge leaf, type A hinges, allow mounting with a very small door gap. Type I hinges are mounted between the door gap. This results in the mounting screws being hidden when the door is closed, which reduces the chance of vandalism.

The hinges are delivered loose and must be mounted according to the accompanying instructions. Any hinge combination may be created (if needed, by shortening the middle wing) thanks to the modular design and available accessories.

see also...

- List of Hinge Types → page 1324
- Product Family Standard Parts for Profile Systems → page 18

On request

- Other lengths and hole spacings
- Other finishes

How to order		1	Width l ₁
		2	Length l ₂
		3	Type
		4	Identification
		5	Finish

GN 2295-72-335-A-C-EL