



- 3 Type**
- S** Continuous adjustment
  - T** Adjustment in 10° steps (serration)
- 4 Identification no.**
- 2** With 2 stainless steel socket cap screws DIN 912

Dimensions in: millimeters - inches

<b>1</b> $d_1$ Bore	<b>2</b> $x_1$	$d_2$	$k$	$l_1$	$m_1$	$m_2$	$t$	$x_2$	$y_1$	$y_2$	$z_1$ Screw location for screw size	$z_2$ Screw location for screw size	<b>Accessory</b> Recommended levers GN 911.9 for $z_1 / z_2$ $l_2$	
B 30	40 1.57	6.5 0.26	45 1.77	106 4.17	33 1.30	42 1.65	8 0.31	-	75 2.95	60 2.36	M8-25	M8-25	63 2.48	78 3.07
B 30	75 2.95	6.5 0.26	45 1.77	106 4.17	33 1.30	67 2.64	8 0.31	60 2.36	75 2.95	60 2.36	M8-25	M8-25	63 2.48	78 3.07

**Specification**

- Body  
Plastic  
Technopolymer (Polyamide PA)  
- Glass fiber reinforced  
- Temperature resistant up to 212 °F (100 °C)  
- Black, RAL 9005, matte finish **● SW**  
- Gray, RAL 7040, matte finish **○ GR**
- Socket cap screws DIN 912  
Stainless steel AISI 304
- Hex nuts DIN 985  
- Stainless steel AISI 304  
- Self-locking with polyamide ring
- Load Rating Information → page QVX
- Plastic Characteristics → page QVX
- Stainless Steel Characteristics → page QVX
- RoHS compliant

**Accessory**

- Adapter bushings EN 290 → page QVX
- Adjustable levers GN 911.9 → page QVX

**Information**

In the initial position, the clamping bore axis of the swivel clamp connector joints EN 282.10 is parallel to the flange surface and can be swiveled by ±90°. It holds typical construction tubes with full surface contact over the entire cross-section of the bore.

At the screw location  $z_1$ , the socket cap screw reduces the bore cross-section for clamping. Adapter bushings EN 290 can be used to reduce the bore cross-sections to smaller diameters.

The screw location  $z_2$  serves for fixing the joint axis, which can be adjusted continuously or in 10° steps, depending on the type.

For clamping without tools, the socket cap screws can be replaced by the adjustable levers GN 911.9 listed in the table as accessories.

see also...

- Construction Tubes GN 990 → page QVX
- Swivel Clamp Connector Bases EN 272.9 → page XYZ
- Swivel Clamp Connectors EN 278.9 → page XYZ

How to order	1 Bore $d_1$
	2 Length $x_1$
	3 Type
	4 Identification no.
	5 Color

**EN 282.10-B30-75-S-2-SW**