





Metric table

Ų	2		2		2		Dimensions in: millimeters - inche						
d₁ Ø Insert	d₂ Thread		d ₃ H7 Bore with keyway		S₁ Square		S2 Hex	b	d ₄	d₅	h	Length I	Max. torque in Nm
12 <i>0.47</i>	M 8	-	-	-	V 8	-	-	22 0.87	9 <i>0.35</i>	20 0.79	11 <i>0.43</i>	118 <i>4.65</i>	40
17 0.67	M 10	M 12	K 10	K 12	V 10	-	SK 12	30 1.18	11 <i>0.43</i>	26 1.02	14 <i>0.55</i>	156 <i>6.14</i>	70
22 0.87	M 14	M 16	K 14	K 16	V 12	V 14	SK 14	39.5 1.56	14 <i>0.55</i>	33 1.30	17 <i>0.67</i>	187 7.36	130
26 1.02	M 20	-	K 18	-	V 17	-	SK 17	46 1.81	17 <i>0.67</i>	33 1.30	22 0.87	219 <i>8.62</i>	180

Specification

- Housing Steel, powder coated Black, matte textured finish
 Wrench arm Stainless steel AISI 303 Matte shot-blasted finish
- Insert
- Steel, hardened
- Domed gear lever knob EN 719.1
 → www.jwwinco.com
 Plastic
 Duroplast (Phenolic PF)
 Black, shiny finish
- Square Bores DIN 79 → page 2044
- Keyways WN / DIN 6885 → page 2040
- ISO Fundamental Tolerances → page 2129
- Stainless Steel Characteristics → page 2143
- RoHS compliant

On request

- Modified inserts
- Other handle lengths

Information

GN 316 ratchet wrenches are robust, easy to handle and have an appropriate and attractive design.

Ratchet wrenches are normally used wherever the same ratchet insert is always required or where it makes sense to leave the ratchet wrench at the place of use. That can mean, attaching it to equipment or machinery as a "stationary" tool. Various versions of ratchet inserts are available, and these can be exchanged as needed by loosening the retaining screw and removing the cover plate.

The ratchet action is deactivated when the reversing lever is in the locked position (central position), allowing torque to be applied in both directions.

see also ...

• Countersunk Washers GN 184 (for Axial Fixing) → page 1150

How to order	1	Insert diameter d ₁
GN 316-26-V17	2	Square bore s ₁ (Hex bore s ₂ , Thread d ₂ , Bore with keyway d ₃)