



Metric table

2 3

Dimensions in: millimeters - inches

d ₁ For rod / tube	h ₁	b	d ₂	d ₃	d ₄	d ₅	d ₆	h ₂	m	A/F	t min.
30 +0.1 / -0.25 1.181 +0.004 / -0.01	60 2.36	27.5 1.08	M 10	46 1.81	46.6 1.83	42 1.65	8 0.31	84 3.31	13.5 0.53	5	20 0.79
40 +0.15 / -0.3 1.575 +0.006 / -0.012	70 2.76	30 1.18	M 12	56 2.20	56.8 2.24	50 1.97	8 0.31	99 3.90	18.5 0.73	5	25 0.98

Specification

- Body
Stainless steel AISI 304 **NI**
Matte finish (Ra < 0.8 µm) **MT**
- Sealing ring and wiper
TPU **T**
- Blue
- Temperature resistant
-4 °F to +230 °F (-20 °C to +110 °C)
- Hardness 95 ±5 Shore A
- FDA compliant
- Clamping wedge
Brass
- Set screw
Stainless steel
- [Plastic Characteristics](#) → page QVX
- [Stainless Steel Characteristics](#) → page QVX
- [RoHS](#)

Accessory

- Hex head screws GN 1580 → page QVX
- Hex head screws GN 1581 → page QVX

Information

Straight handle legs GN 3331 are intended for use in hygienic areas. The sealed mounting surface enables fastening without dead spaces. The high quality finish as well as the non-concave geometry prevent adherence of dirt and facilitate cleaning.

The straight handle legs are designed for use with tubular handles GN 3330 to reduce large distances between mounting points or excessive loads on the handle legs. Regardless of the handle application, supports can be used to fix rods and tubes with the corresponding diameter d₁. The tube or rod is fastened during installation using the integrated clamping wedge.

see also...

- [Product Family Hygienic Design](#) → page QVX
- [Tubular Handles GN 3330 \(Stainless Steel, Hygienic Design\)](#) → page QVX

How to order	
1	Material
2	Diameter d ₁
3	Height h ₁
4	Finish
5	Material (seals)

1 2 3 4 5

GN 3331-NI-40-70-MT-T

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4