# Hollow Knurled Screws

Plastic, with Stainless Steel Threaded Stud, with Brass / Plastic Tip

JW WINCO® A Ganter Company









**Metric**

SS Stainless Steel

## Metric table

Dimensions in: millimeters / inches

| $d_1$ | $l_1$ Nominal length | | | | | $l_2$ | | $d_2$ | | $d_3$ | $d_4$ | $d_5$ | h | k |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | MS tip | KU tip | MS tip | KU tip | | | | | |
| M 5 | 10<br>0.39 | 15<br>0.59 | 20<br>0.79 | 25<br>0.98 | - | 0.5<br>0.02 | 1<br>0.04 | 3<br>0.12 | 3<br>0.12 | 19<br>0.75 | 9<br>0.35 | 12<br>0.47 | 14<br>0.55 | 8<br>0.31 |
| M 6 | 10<br>0.39 | 16<br>0.63 | 20<br>0.79 | 25<br>0.98 | 30<br>1.18 | 1<br>0.04 | 1.3<br>0.05 | 4<br>0.16 | 3.5<br>0.14 | 24<br>0.94 | 12<br>0.47 | 14<br>0.55 | 16.5<br>0.65 | 9.5<br>0.37 |
| M 8 | 20<br>0.79 | 25<br>0.98 | 30<br>1.18 | 40<br>1.57 | - | 1.5<br>0.06 | 1.6<br>0.06 | 6<br>0.24 | 5<br>0.20 | 30<br>1.18 | 14<br>0.55 | 16<br>0.63 | 19.5<br>0.77 | 11<br>0.43 |

### Specification

**Knob**
Plastic, Polyamide (PA)
Black, shiny finish

**Threaded stud**
- Stainless steel AISI 304 Cu
- Tip
  - Brass **MS**
  - Plastic (Polyacetal POM) **KU**

RoHS

Hollow knurled screws GN 421.10 with brass or plastic tip are used in applications where marks and damages on the workpiece are unacceptable.

| see also... | Page |
|---|---|
| **GN 6336.10** Star Knobs (with Brass / Plastic Tip) | QVX |
| **GN 7336.5** Hollow Knurled Knobs (with Brass / Plastic Tip) | QVX |
| **GN 653.10** Knurled Thumb Screws (with Brass / Plastic Tip) | QVX |
| **GN 421** Hollow Knurled Screws (with Loss Protections GN 111.7) | QVX |

**Technical Information**

| | |
|---|---|
| Plastic Characteristics | QVX |
| Stainless Steel Characteristics | QVX |

How to order

GN 421.10-M8-25-MS

| | |
|---|---|
| 1 | Thread $d_1$ |
| 2 | Length $l_1$ |
| 3 | Tip material |



⚠ WARNING: Cancer and Reproductive Harm — www.P65Warnings.ca.gov