



Metric table

Dimensions in: millimeters - inches

d ₁	Length l ±0.5							d ₂ Thread	d ₃	h	r	t min.
	32	45	55*	64	88*	-	-					
6 0.24	1.26	1.77	2.17	2.52	3.46	-	-	M 3	9 0.35	26 1.02	7 0.28	7 0.28
8 0.31	2.17	2.52	3.46	3.78	3.94	120*	128 5.04	M 4	12 0.47	35 1.38	10 0.39	8 0.31
10 0.39	3.46	3.94	4.72	7.09	7.87	200	235*	M 5	15 0.59	43 1.69	12 0.47	12 0.47
12 0.47	4.92	6.30	7.87	9.84	-	-	-	M 6	-	51 2.01	14 0.55	12 0.47
16 0.63	6.30	7.87	9.84	11.81	-	-	-	M 6	-	59 2.32	18 0.71	12 0.47

* Suitable for 19" rack and enclosure layout

Specification

- Steel
 - Powder coated
 - Black, RAL 9005, textured finish **SW**
 - Chrome plated finish **CR**
 - Blackened finish **BT**
- Location disks
 - Zinc die-cast, nickel plated
- Load Rating Information → page 2068
- RoHS compliant

Information

Cabinet U-handles GN 425.1 are manufactured from a bent steel profile. Cabinet U-handles with Ø d₁ = 6, 8 and 10 mm are supplied with two location disks to guarantee a perfect location even with large holes in the cabinet. The location disks are enclosed in the package with the handle.

The stainless steel version is preferred over the chrome plated version in steel for outdoor applications.

see also...

- Cabinet U-Handles GN 425.1 (Offset Round Steel) → page 145

On request

- Various metric size fasteners and kit packaging

How to order	1	Handle diameter d ₁
	2	Length l
	3	Finish
GN 425-10-120-CR		