Threaded Plugs

Plastic





Metric



elesa
Original design THR.

3 Identification no.

1 Without vent hole

Metric table

1 2 Dimensions in: millimeters / inches

d_1	d_2	l_1	l_2	s
32 1.26	G 1/2	29 1.14	11 0.43	4 0.16
37 1.46	G 3/4	32.5 1.28	12 0.47	5 0.20
44 1.73	G 1	36 1.42	13 0.51	6 0.24

Specification 4

Threaded plug
Plastic, Polyamide (PA)
Black, matte finish ● **B**

O-ring
Acrylonitrile butadiene rubber (NBR)

Operating temperature
-22 °F to +212 °F (-30 °C to +100 °C)

RoHS

Threaded plugs EN 443 with the external diameter d_1 match the screw-in holes for DIN 3852 pipe fittings.
The O-ring is embedded in a radial groove on the flat side. This protects against loss and prevents it from being squeezed out during tightening.

see also...	Page
GN 741 Fluid Fill / Drain Plugs	QVX
GN 742 Fluid Fill / Drain Plugs (with External Hex)	QVX
EN 745 Threaded Plugs	QVX
EN 745.2 Threaded Plugs (with Seal / with O-ring)	QVX
GN 441 Threaded Plugs (with Finger Grip)	QVX
GN 442 Threaded Plugs (Aluminum)	QVX
EN 443.13 Threaded plugs (Plastic, with Loss Protection)	QVX
EN 548.1 Fluid Fill Plugs (Plastic)	QVX

Technical Information

Plastic Characteristics QVX

Accessory

GN 7490 Weld Bushings (Steel / Stainless Steel) QVX

How to order

1 2 3 4
EN 443-44-G1-1-B

1	Diameter d_1
2	Thread d_2
3	Identification no.
4	Color

⚠ **WARNING**: Cancer and Reproductive Harm — www.P65Warnings.ca.gov