



Specification

- Star knob Plastic Technopolymer (Polyamide PA) Shock-resistant, black, matte finish	ST
- Star knob Plastic Duroplast (Phenolic PF) Black, shiny finish (only available in metric sizes)	SK
- Threaded stud Steel, zinc plated, blue passivated finish	
• <i>Plastic Characteristics</i> → page 2135	
• RoHS compliant	

On request

- Special shorter than listed stud lengths and various stud tips

Information

GN 6336.4 star knobs comply with DIN 6336 type L.

see also...

- *Star Knobs GN 6336.10 (with Brass or Nylon Tip)* → page 582
- *Star Knobs GN 6336.12 (with Toggle Thrust Pad)* → page 583
- *Star Knobs GN 6336.13 (with Loss Protection)* → page 584
- *Star Knobs GN 6336.4 with Loss Protection GN 111.7* → page 2046

How to order

GN 6336.4-ST-25-1/4X20-15

1	Material
2	Handle diameter d_1
3	Thread d_2
4	Length l

Inch table

Dimensions in: inches - millimeters

d ₁	d ₂	Length l ≈						d ₃	h ₁	h ₂
		Material ST								
0.98 25	1/4 x 20	0.59 15	0.87 22	1.10 28	-	-	-	0.47 12	0.63 16	0.31 8
1.26 32	1/4 x 20	0.43 11	0.63 16	0.71 18	0.94 24	1.22 31	1.46 37	0.55 14	0.79 20	0.39 10
1.57 40	5/16 x 18	0.79 20	0.91 23	1.26 32	1.42 36	1.89 48	-	0.71 18	0.98 25	0.51 13
1.97 50	3/8 x 16	0.98 25	1.18 30	1.57 40	1.69 43	2.17 55	-	0.87 22	1.26 32	0.67 17
2.48 63	1/2 x 13	-	-	-	-	-	-	1.02 26	1.57 40	0.83 21

Metric table

Dimensions in: millimeters - inches

d ₁	d ₂	Length l ≈										d ₃	h ₁	h ₂							
		Material ST													Material SK						
25 0.98	M 5	10 0.39	15 0.59	20 0.79	25 0.98	30 1.18	-	-	-	-	-	10 0.39	15 0.59	20 0.79	25 0.98	-	-	-	12 0.47	16 0.63	8 0.31
25 0.98	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	45 1.77	60 2.36	-	-	-	-	-	-	-	-	-	12 0.47	16 0.63	8 0.31
32 1.26	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	45 1.77	60 2.36	-	-	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	45 1.77	14 0.55	20 0.79	10 0.39
32 1.26	M 8	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	55 2.17	60 2.36	-	-	-	-	-	-	-	-	14 0.55	20 0.79	10 0.39
40 1.57	M 8	16 0.63	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	55 2.17	60 2.36	-	16 0.63	20 0.79	25 0.98	30 1.18	40 1.57	55 2.17	-	18 0.71	25 0.98	13 0.51
40 1.57	M 10	15 0.59	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	45 1.77	50 1.97	55 2.17	60 2.36	-	-	-	-	-	-	-	18 0.71	25 0.98	13 0.51
50 1.97	M 10	15 0.59	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	45 1.77	50 1.97	55 2.17	60 2.36	25 0.98	30 1.18	35 1.38	45 1.77	55 2.17	-	-	22 0.87	32 1.26	17 0.67
50 1.97	M 12	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	60 2.36	-	-	-	-	-	-	-	-	-	-	22 0.87	32 1.26	17 0.67
63 2.48	M 12	20 0.79	25 0.98	30 1.18	35 1.38	40 1.57	50 1.97	60 2.36	-	-	-	30 1.18	35 1.38	40 1.57	50 1.97	60 2.36	-	-	26 1.02	40 1.57	21 0.83
80 3.15	M 16	-	-	-	-	-	-	-	-	-	-	30 1.18	40 1.57	50 1.97	60 2.36	70 2.76	-	-	35 1.38	50 1.97	25 0.98

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

