



**Inch table**

Dimensions in: inches - millimeters

| <sup>1</sup> d <sub>1</sub> | <sup>2</sup> d <sub>2</sub> | <sup>3</sup> Length l | d <sub>3</sub> | h <sub>1</sub> | h <sub>2</sub> |
|-----------------------------|-----------------------------|-----------------------|----------------|----------------|----------------|
| 0.83<br>21                  | 10 x 32                     | 0.75<br>19            | 0.49<br>12.5   | 0.71<br>18     | 0.41<br>10.5   |
| 0.98<br>25                  | 1/4 x 20                    | 0.75<br>19            | 0.57<br>14.5   | 0.89<br>22.5   | 0.55<br>14     |
| 1.22<br>31                  | 5/16 x 18                   | 0.75<br>19            | 0.73<br>18.5   | 1.06<br>27     | 0.67<br>17     |

**Metric table**

Dimensions in: millimeters - inches

| <sup>1</sup> d <sub>1</sub> | <sup>2</sup> d <sub>2</sub> | <sup>3</sup> Length l | d <sub>3</sub> | h <sub>1</sub> | h <sub>2</sub> |
|-----------------------------|-----------------------------|-----------------------|----------------|----------------|----------------|
| 16<br>0.63                  | M 3                         | 10<br>0.39            | 16<br>0.63     | -              | -              |
| 18<br>0.71                  | M 4                         | 10<br>0.39            | 16<br>0.63     | -              | -              |
| 21<br>0.83                  | M 5                         | 10<br>0.39            | 16<br>0.63     | 20<br>0.79     | -              |
| 21<br>0.83                  | M 6                         | 16<br>0.63            | 20<br>0.79     | 30<br>1.18     | -              |
| 25<br>0.98                  | M 6                         | 16<br>0.63            | 20<br>0.79     | 25<br>0.98     | 30<br>1.18     |
| 25<br>0.98                  | M 8                         | 20<br>0.79            | 25<br>0.98     | 30<br>1.18     | 40<br>1.57     |
| 31<br>1.22                  | M 8                         | 20<br>0.79            | 25<br>0.98     | 30<br>1.18     | 40<br>1.57     |
| 31<br>1.22                  | M 10                        | 30<br>1.18            | 40<br>1.57     | -              | -              |

**Specification**

- Plastic  
Technopolymer (Polyamide PA)  
- Glass fiber reinforced  
- Temperature resistant up to 266 °F (130 °C)
- Color  
Black-gray, RAL 7021, matte finish ● SG
- Threaded stud  
Steel, zinc plated, blue passivated finish
- Plastic Characteristics → page 2135
- RoHS compliant

**Information**

When used as a push-pull button, the thumb rests naturally on the concave front surface, making it easier to grip the EN 676 knurled knob. The slight knurling on the rim of the knob makes tightening or clamping operations easier.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- Product Family Ergostyle® → page 18
- Mushroom Shaped Knobs GN 76 → page QVX

|                                    |   |
|------------------------------------|---|
| How to order (Inch)                | <sup>1</sup> Handle diameter d <sub>1</sub> |
| <sup>2</sup> EN 676-21-10X32-19-SG | <sup>2</sup> Thread d <sub>2</sub>          |
|                                    | <sup>3</sup> Stud length l                  |
|                                    | <sup>4</sup> Color                          |

|                                 |   |
|---------------------------------|---|
| How to order (Metric)           | <sup>1</sup> Handle diameter d <sub>1</sub> |
| <sup>2</sup> EN 676-31-M8-25-SG | <sup>2</sup> Thread d <sub>2</sub>          |
|                                 | <sup>3</sup> Stud length l                  |
|                                 | <sup>4</sup> Color                          |